



B-038.201P (B-038-1)

| REV. | REVISIONS | REC. | DATE | REV. | REVISIONS | REC. | DATE |
|------|-----------|------|------|------|-----------|------|------|
|      |           |      |      |      |           |      |      |
|      |           |      |      |      |           |      |      |
|      |           |      |      |      |           |      |      |

|  |                 |                   |                      |  |                                |  |
|--|-----------------|-------------------|----------------------|--|--------------------------------|--|
| DRAWN & DRAFTED BY<br>JOHN   | TOLERANCES      |                   | ANGLE: $\pm 1^\circ$ | TITLE:<br>T-H BOBBIN EP-10 (2 GROOVES) |                                |  |
|  | 0 < L ≤ 4 ±0.1  | pin pitch<br>±0.2 | UNIT: MM             | BOBBIN MATERIAL:<br>PHENOLIC (PM-9630) | UL REC.<br>UL 94V-0            |  |
| CHECKED & APPROVED BY<br>JOHN RONG   | 4 < L ≤ 16 ±0.2 |                   | ORIGIN: DG           | PIN MATERIAL:<br>CP WIRE               | PIN TENSION LOAD:<br>1.0KG MIN |  |
| LEPCOS (NWL) <a href="http://ferrite.ru">http://ferrite.ru</a><br>Pin Shine Industrial Co bobbin |                 |                   | DATE: OCT.20 '2004   | DRAWING NO. P-1009-1                   | REV. 0                         |  |