

FORM Identifier: F 108 Revision: 04 Page: 1/1	Product specification for inductive components	MAGNETEC GmbH Industriestrasse 7 D-63505 Langenselbold
---	--	---



Client:	MAGNETEC GmbH	Magnetec P/N:	M-333	Magnetec A/N:	12367
Client's P/N:	/	PS Index:	02	PS Revision:	03
Subject:	WANDLER			Type:	E

1. Mechanical Outline	
Nominal core dimensions: 50,0 x 45,0 x 5,0 Finished product dimensions: OD ≤ 52,2 ID ≥ 41,8 H ≤ 7,5 [dimensions] = mm	

2. Core data (nominal values)			
Core material:	NANOPERM®	$L_{Fe} = 14,91 \text{ cm}$	$A_{Fe} = 0,09 \text{ cm}^2$
Permeability level:	30 000	@ frequency 10 kHz	@ H peak 2,8 mA/cm

3. Inspection values				
	Measured value	Measurement limits	Frequency	leff x N [mA x turn]
	AL [μH]	1,6 - 3,3	10 kHz	30
	AL [μH]	0,8 - NA	100 kHz	30

4. Core finishing	
Type:	Cased
Marking:	MAGNETEC M-333-02 YM (YM = Year/Month), acc. to IEC 60062 6.1.1
Packaging:	15 pcs. per layer; 9 layers per carton box ; PU = 135 pcs.

5. Comments:	

Index / Revision	Alteration	Date
02 / 01	Product Specification	05.10.2006
02 / 02	Packaging: PU = 135 pcs	08.11.2006
02 / 03	100kHz lower limit defined	25.07.2014

Created:	Z. Palánki	Approved (Techn):	F. Záborszky	Approved (Quality):	J. Gulyás	Released:	T. Trupp
	25.07.2014		01.08.2014		01.08.2014		01.08.2014